

## MH SERIES COMPACT, STAINLESS STEEL CONSTRUCTION

Sterling's MH Series machine hopper loaders offer a unique mass flow and compact design. MH machine hoppers can be insulated or non-insulated (0.85 and 1.7 cu. ft. models only) and have a hinged access door (3.0 cu.ft and larger models) for easy access and maintenance.



### Features

- Compact design
- Hinged access door (3.0 cu. ft. [85 liters] and larger models)
- Slide gate
- Stainless steel construction
- Insulated construction (0.85 and 1.7 cu. ft. models [25 and 50 liter] only)
- Easy-view Lexan sight glass ®
- Adjustable quick-release clamp design
- Cover selections available for mounting various loaders configurations

### Options

- Premium machine-mount slide gate
- Flange transition, 7" to 4" square
- Drawer magnet with slide gate; 0.85 to 6.0 cu. ft. (25 to 170 liters) (7" x 7" square flange)
- Blank cover
- Manual fill cover
- Vacuum hopper cover
- Manual fill cover



## MH SERIES

### SPECIFICATIONS

Model	MHx.x				
	0.85*	1.7*	1.7 w/ door	3.0	6.0
Capacity (cu. ft./l)	0.85/25	1.7/50	1.7/50	3.0/85	6.0/170
Square flange	7" x 7" (178 x 178 mm)				
Insulated dia., in. (mm)	14 (356)	14 (356)	16 (406)	22 (559)	22 (559)

\* Consult factory for non-insulated supply hoppers

